

Bare Copper

Soft Drawn Bare Copper Wire



Meets or exceeds
**ASTM-B3, ASTM-
B8, or ASTM-B787**

APPLICATIONS

For use in overhead transmission and distribution applications. Also for use in grounding applications.

CONDUCTORS

Solid conductors uncoated copper per ASTM-B3

Stranded conductors 8 AWG – 2 AWG and 250 MCM – 750 MCM uncoated copper per ASTM-B3 and ASTM-B8

Stranded conductors 1 AWG – 4/0 AWG – uncoated copper conductors per ASTM B3 and ASTM-B787

INDUSTRY STANDARDS*

ASTM B3

ASTM B8

ASTM-B787

RoHS Compliant



MADE IN THE USA

©2012, Cerro Wire LLC
All Rights Reserved

*It is the sole responsibility of the end user to determine suitability of this product for its intended end use and application.

Bare Copper

Soft Drawn Bare Copper Wire

Product Code Number	AWG Size	No. of Strands	Diam. Each Inches	Approx. Overall Diam. Inches	Approx. Net Wt. Lbs./M Ft.
050-2000x	8	Solid	.1285	.1285	50
050-2215x	6	Solid	.1620	.1620	79
050-2200x	6	Solid	.1620	.1620	79
050-2400x	4	Solid	.2043	.2043	126
050-2600x	2	Solid	.2576	.2576	201
050-4000x	8	7	.0486	.146	50
050-4200x	6	7	.0612	.184	80
050-4215x	6	7	.0612	.184	80
050-4400x	4	7	.0772	.232	127
050-4600x	2	7	.0974	.292	202
050-4700x	1	19	.0710, .0568	.323	255
050-5000x	1/0	19	.0807, .0591	.360	323
050-5200x	2/0	19	.0906, .0663	.404	404
050-5400x	3/0	19	.1017, .0745	.454	509
050-5600x	4/0	19	.1142, .0836	.510	643
050-6000x	250	37	.0850, .0654	.545	744
050-6400x	300	37	.0935, .0701	.597	895
050-6800x	350	37	.1000, .0799	.644	1,040
050-7200x	400	37	.1077, .0815	.686	1,170
050-8000x	500	37	.1192, .0973	.786	1,484
050-8400x	600	61	.0989	.866	1,792
050-8800x	750	61	.1114	.968	2,285

Bare Copper

Soft Drawn Bare Copper Wire

Package Code	D	H	I	J	K	P	S*	X*
AWG Size	125' Spool	200' Spool	315' Spool	500' Reel	1,000' Reel	5,000' Reel	SPEC Size	SPEC Cut Avail.
8 Solid				X		X		
6 Solid			X		X	X		
4 Solid		X		X	X			
2 Solid	X							
8-7 STR				X	X			
6-7 STR			X		X			
4-7 STR		X			X			
3-7 STR								
2-7 STR	X				X			
1-19 STR								X
1/0-19 STR				X	X			
2/0-19 STR				X	X			
3/0-19 STR				X	X			
4/0-19 STR				X	X			
250-37 STR								X
350-37 STR								X
500-37 STR								X
750-37 STR								X

* No special cuts less than 50'