

Bare Copper

Soft Drawn Bare Copper Wire



- Meets or exceeds ASTM-B3, ASTM-B8, or ASTM-B787

APPLICATIONS

For use in overhead transmission and distribution applications. Also for use in grounding applications.

CONDUCTORS

Solid conductors uncoated copper per ASTM-B3

Stranded conductors 8 AWG – 2 AWG and 250 MCM – 750 MCM uncoated copper per ASTM-B3 and ASTM-B8

Stranded conductors 1 AWG – 4/0 AWG – uncoated copper conductors per ASTM B3 and ASTM-B787

INDUSTRY STANDARDS*

ASTM B3

ASTM B8

ASTM-B787

RoHS Compliant



MADE IN THE USA

*It is the sole responsibility of the end user to determine suitability of this product for its intended end use and application.

©2012, Cerro Wire LLC, All Rights Reserved

AWG Sizes	No. of Strands	Diam. Each Inches Individual Strand Diameter (in.)	Approx. Overall Diam. (in.)	Approx. Net Wt. Lbs./M Ft.	Standard Packaging
8	Solid	.1285	.1285	50	500' 1000' 2500' 5000' reels
6	Solid	.1620	.1620	79	315' 500' 1000' 2500' 5000' reels
4	Solid	.2043	.2043	126	200' 500' 1000' 2500' 5000' reels
2	Solid	.2576	.2576	201	125' reels
8	7	.0486	.146	50	500' 1000' 2500' 5000'reels
6	7	.0612	.184	80	315' 500' 1000' 2500' 5000'reels
4	7	.0772	.232	127	200' 500' 1000' 2500' 5000'reels
2	7	.0974	.292	202	125' 500' 1000' 2500' 5000'reels
1	19	.0710, .0568	.323	255	500' 1000' 2500' 5000' reels
1/0	19	.0807, .0591	.360	323	500' 1000' 2500' 5000' reels
2/0	19	.0906, .0663	.404	404	500' 1000' 2500' 5000' reels
3/0	19	.1017, .0745	.454	509	500' 1000' 2500' 5000' reels
4/0	19	.1142, .0836	.510	643	500' 1000' 2500' 5000' reels
250	37	.0850, .0654	.545	744	Special Cut Available
300	37	.0935, .0701	.597	895	Special Cut Available
350	37	.1000, .0799	.644	1,040	Special Cut Available
400	37	.1077, .0815	.686	1,170	Special Cut Available
500	37	.1192, .0973	.786	1,484	Special Cut Available
600	61	.0989	.866	1,792	Special Cut Available
750	61	.1114	.968	2,285	Special Cut Available