



Innovation That Lowers Your:

- Inventory Investment
- Handling Costs
- Inventory Shrink
- Installation Cost
- Environmental Impact

SLiPWire™ XLP is jacketed with Cerro's self lubricating polymer which reduces the time, labor and cost for installation, eliminates the materials and labor for lubricating the wire and messy clean-up further reducing costs, and creates a safer workplace. SLiPWire™ is also RoHS Compliant.



We do the Math, so you don't have to!

True Sequential Footage™ cable is unlike other sequential printed cables. It provides accurate footage beginning at 0 at the bottom of the reel and ends with the finished length at the top of each reel. With True Sequential Footage™ you know where to cut for a precise, accurate length and how many feet are left on the original reel at a glance. That's inventory and length cost control. And with Cerrowire's Max Print® identification system you'll easily know the size of the cable, which aids in selection, inspection and prevents costly errors. Available with Cerrowire Advantage™.



1099 Thompson Road, SE
Hartselle, AL 35640
Phone: 800.523.3869

- 90°C Dry or Wet/600 Volts
- Gasoline and Oil Resistant II
- Machine Tool Wire: 90°C Dry
- Appliance Wire: 105°C Dry
- Rated THHN/THWN-2: 90°C Dry or Wet

APPLICATIONS

- 600 volt building wire for use in commercial and industrial applications as specified in the NEC[®]
- 8-1 AWG is marked VW-1
- 1/0-750 MCM rated for CT use
- 1 AWG - 750 MCM in black; Rated sunlight resistant
- Pulling lube is not required. Jacketed with SLP[™] (Self-Lubricating Polymer).

CONDUCTORS

- Uncoated copper per ASTM-B3, ASTM-B787 (6 AWG-500 MCM) & ASTM-B8 (600 MCM-750 MCM)

INSULATION

- Color coded, heat and moisture resistant PVC (polyvinyl chloride)

SLP-JACKET[™]

- Using Cerro Wire's SLPJacket[™] (Self-Lubricating Polymer) Technology, Cerro Wire SLPWire[™] THHN is self lubricated.
- Nylon (polyamide), color coded

INDUSTRY STANDARDS

- UL 83: File No. E15119
- Canadian Standard C22.2 No. 75 and CSA Bulletin No. 1451
- ASTM: B3, B8, B787
- WC70/ICEA S-95-658
- Federal Specification A-A-59544
- NFPA70: National Electrical Code[®]
- Sample: CERRO WIRE VINYLON-A 350 KCMIL (UL) MTW OR THWN-2 OR THHN OR GASOLINE AND OIL RESISTANT II OR AWM FOR CT USE SUNLIGHT RESISTANT 600V—CSA TWN75 OR T90 NYLON

Self Lubricating Polymer

- No pulling lube required - 8 AWG and larger
- Sequential footage markings — 1 AWG and larger
- Max Print[®] for easy ID - 1/0 AWG and larger
- Available with Cerrowire Advantage[™]

Vinylon[®] PVC/Nylon
8 AWG—750 MCM

Product Code	Conductors		Covering		Approx O.D. Inches	Allowable Ampacities*			Approx Net Wt. lbs./m ft.
	AWG Size	No. of Strands	PVC Ins. Mils.	Nylon Jkt. Mils.		60°C **	75°C ***	90°C ****	
112-40XX	8	19	30	5	0.217	40	50	55	63
112-42XX	6	19	30	5	0.253	55	65	75	96
112-44XX	4	19	40	6	0.322	70	85	95	153
112-45XX	3	19	40	6	0.350	85	100	110	190
112-46XX	2	19	50	7	0.380	95	115	130	233
112-47XX	1	19	50	7	0.440	110	130	150	299
112-50XX	1/0	19	50	7	0.480	125	150	170	371
112-52XX	2/0	19	50	7	0.524	145	175	195	459
112-54XX	3/0	19	50	7	0.575	165	200	225	571
112-56XX	4/0	19	50	7	0.630	195	230	260	710
112-60XX	250	37	60	8	0.700	215	255	290	848
112-64XX	300	37	60	8	0.750	240	285	320	1,006
112-68XX	350	37	60	8	0.802	260	310	350	1,166
112-72XX	400	37	60	8	0.847	280	335	380	1,324
112-80XX	500	37	60	8	0.930	320	380	430	1,640
112-84XX	600	37	70	9	1.030	355	420	475	1,988
112-88XX	750	37	70	9	1.136	400	475	535	2,459

XX Color Add Code (see below)

* Per Table 310-16 NEC[®]

** For termination to equipment for circuits rated 100 amperes or less, or marked for size 14 through 1 AWG conductors.


*** For termination to equipment for circuits rated over 100 amperes or marked for conductors larger than 1 AWG.

**** For THHN used in dry locations and THWN-2 used in wet or dry locations. For ampacity derating purposes.

Color availability:

All sizes are available in the following colors (color add code is as follows):

Black - 01, White - 02, Red - 03, Blue - 04, Green- 05, Orange - 06, Yellow - 07, Brown- 08, Gray - 10.



Made in USA



LISTED
Rev 01-02-13